

2024 Plow Truck Specifications

FRONT END

- . 20,000 lb. Front Axle
- . 315/80R 22.5 20 Ply Front Tires
- . Hub Piloted Wheels
- . Dual Steering Boxes

ENGINE

- . Minimum - 400 Horse Power
- . Minimum – 1650 Ft. / lbs. Torque
- . Must Meet Minimum EPA requirements
- . Must have PTO Adapter
- . Jacobs Engine brake

TRANSMISSION

- . Allison Automatic that matches the Torque

REAR ENDS

- . 46,000 Lb. Rear ends
- . Power Divider
- . Full Lockers
- . 11R x 22.5-16 Ply Tires
- . Hub Piloted Wheels
- . Gear Ratio not to exceed 65 mph
- . Hendrickson Spring Suspension

CAB

- . Air Ride Drivers Seat with Arm Rests
- . Power Passenger Window
- . Power Mirrors
- . Heated Mirrors
- . Blue Tooth Radio
- . Storage Compartments
- . Visor
- . Air Valve for Trailer
- . Wiring to Front for Plow Lights
- . Led Cab Lights
- . Heated Windshield
- . Gel Batteries to be located under passenger seat
- . Master Switch
- . Minimum of six Auxiliary Switches

FRAME

- . Heavy Single Frame
- . 106” CBC to center of Tandems
- . Front Extension for Plow Frame