

# Sander Body and Plow Equipment

- Tilting Plow Frame with quick connect and air operated front remote.
- 11 Ft. Power Angle Stainless Steel front plow, with trip edge and carbide cutting edge and cover blade.
- 11 Ft. Stainless Steel wing with cutting edges.
- Hydraulic front wing post with trip mechanism.
- Hydraulic patrol for the rear of the wing.
- 74cc load sense front mount hydraulic pump with low oil shut off and override.
- Six section valve control, with cable controls and air activated front remote.
- 40 gallon stainless steel hydraulic tank installed behind the cab, below the rear window with shut off valve and low oil sensor.
- All hard piping must be stainless steel.
- 10. Muncie 300 electronic spreader control.
- 11. Lighting system shall be all LED and include the following.
  - Heated Plow Lights
  - Work lights for spinner, wing, and hopper.
  - Marker Lights
  - Strobes in cab shield corners facing forward.
  - Strobes in rear corner post.
  - Stop/Tail and turns in rear corner post.
  - Back up in rear corner post.
  - 2 Additional Back ups in rear.
- 12 ft. Hardox side tipping all season body.
- The whole body shall be Hardox AR 450 steel.
- Rear corner post shall be stainless steel.
- Cab shield
- Central location for all grease points.
- Electric load cover with aluminum arms.
- Electric jack for feed gate.
- 10" channel side boards with angle welded to top.
- Fold down ladder with grab handles.
- Shovel holder.
- Fold down doors to cover conveyer chain.
- Pintle plate, hook and D rings rated for 20 ton trailer.
- Electric plug and glade hands for trailer.
- One additional conveyer chain, gearbox, electric jack for feed gate, spinner and spinner shaft and all bearings, shafts and sprockets for one conveyer system replacement.